

Ossi Connectors A/S

D-Sub Connector Terms



D-sub Connector Terms

- **HD:** High Density
DE Shell 09-way HD DE Shell 15-way
DA Shell 15-way HD DA Shell 26-way
DB Shell 25-way HD DB Shell 44-way
DC Shell 37-way HD DC Shell 62-way
DD Shell 50-way HD DD Shell –
- **Filtered:** To suppress electro-magnetic interference (EMI) or radio frequency interference (RFI).
- **IDC:** Insulation Displacement Connection, MIL-DTL-24308/27.
- **IEC:** International Electromechanical Commission.
- **MIL:** Military (Department of Defence Standard (DOD)).
- **MIL-C-24308:** Connectors, Electrical, Rectangular, Miniature, Polarized Shell, Rack and Reel, Shield, Straight and Deep.
- **MIL-DTL-24308:** Sub-standard of MIL-C-24308. DTL stand for Detail Specification Sheet.
- **REACH:** Registration, Evaluation, Authorisation and restriction of Chemicals. Regulation (EC) No 1907/2006.
- **RoHS:** Restriction of Hazardous Substances. Regulation (EC) No 2002/95/EC.
- **SMD:** Surface mount Device, any non-through-hole component.
- **SMT:** Surface Mount Technology.
- **THR:** Through Hole Reflow, Pin in Paste.
- **WEEE:** Waste Electrical and Electronic Equipment Directive. Regulation (EC) No 2002/96.



For further information

We kindly ask you to contact Ossi Connectors A/S at:

Tel: +45 54 78 28 88

Fax: +45 54 78 33 40

E-mail: info@ossi.dk