

KK2A Panel Versions (2 HU)

Connector	Number of cut-outs
Sub-D9	8 10 12 16 20
Sub-D15	8 10 12 16 20
Sub-D25	8 10 12 16 20
Sub-D37	8 10 12 16 20
Sub-D50	8 10 12 16 20
BNC-BU (8.9 X 9.7 mm)	8 10 12 16 20 24 32
BNC-IN (12.0 X 12.9 mm)	8 10 12 16 20 24 32
Twinax	8 10 12 16
DIN-Audio	8 10 12 16 20 24 32
XLR	8 10 12 16 20 24 32
RJ11 - 45 (12.9 X 14.8 mm)	8 10 12 16 20 24 32
RJ11 - 45 (12.9 X 15.5 mm)	8 10 12 16 20 24 32
RJ11 - 45 (14.8 X 20.1 mm)	8 10 12 16 20 24 32
RJ11 - 45 (14.8 X 20.6 mm)	8 10 12 16 20 24 32
RJ11 - 45 (20.3 X 20.3 mm)	8 10 12 16 20 24 32
F-SMA (7.0 X 7.5 mm)	18 20 24 32 40
SC	18 20 24 32 40
SC-Duplex	18 20 24
ST (7.8 X 9.6 mm)	18 20 24 32
ST-Duplex	18 20 24
D-11	Blank panel
SIG-S	Identification label strip

Consult factory when ordering:

- Printed and or painted panels for layout and part number
- Other configurations of connector cut-outs than listed above