




D-Sub Backshells DTPPK-Series

TECHNICAL SPECIFICATIONS

Material:	Polycarbonate UL94 V0
Temp. range:	-55°C - 105°C
Cable strain relief:	Grommets 4, 5, 7 and 9 mm, Polycarbonate UL94 V0
Cable diameter:	3.0 - 13.0 mm
Locking screws:	Long jackscrews with moulded plastic knob for colour coding. UNC4-40 as standard. M2.5, M2.6 and M3.0 are optional
Cable outlet:	Straight



TYPE	A	B
DTPPK9	31	38,3
DTPPK15	39,3	40,5
DTPPK25	53	47,8
DTPPK37	69,5	52,2

PART NUMBERING SYSTEM

DTPPK25 - M2.6 - RED - K

Series: _____
 DTPPK
 Size: _____
 9, 15, 25 or 37
 Thread (jackscrew): _____
 Omit = UNC 4-40
 M2.5
 M2.6
 M3.0

Packaging:
 K = Kit package
 BULK = Bulk package / 100 pcs
 Colour:
 Omit = Black
 Other colours available: beige, blue, brown,
 green, grey, ivory, red, white and yellow

FEATURES

- Available in sizes 9, 15, 25 and 37
- Light weight and cost effective
- Compact and attractive design
- Re-openable
- Company logotype available upon request
- Long jackscrews with UNC 4-40 thread as standard, M2.5, M2.6 or M3.0 are optional
- For custom designed solutions, please consult factory